EOC1121R4L

EOC Slave, Wodaplug



Slave zariadenie, ktoré má jeden káblový TV vstup a Ethernet dátový hybridný vstupný port, jeden káblový televízny výstupný port a jeden konektor RJ45 Ethernet port pre prístup k dátam.

Vlastnosti:

- Remote Management cez EOC Master zariadenie
- QOS podpora
- VLAN podpora
- Up & Downstream bandwidth obmedzenia
- Dynamická alokácia pásma
- Automatická konfigurácia cez Master zariadenie
- Auto aktualizácia prostredníctvom Master zariadenia
- Jednoduchá inštalácia
- Vstupný VF port cez F-konektor
- Výstupný VF port pre TV cez F-konektor
- 2 LAN porty cez RJ45
- Externý napájací zdroj

XD VISION, s.r.o.
Vyšehradská 8
851 06 Bratislava
www.xdvision.sk

pob. Matúškova 7
026 01 Dolný Kubín
Tel.: +421 43 5111 272,3
Fax: +421 43 5111 274
www.xdvision.sk
satdk@xdvision.sk

Parametre	Špecifikácie
Model	220V (220V Power supply), 60V (60V Power Suply)
Protocol of Network	IEEE802.3, IEEE802.3u, IEEE HomePlug BPL, VLAN(IEEE802.1Q), QoS (802.1p)
PHY Speed	200Mbps
Frequency Range	7-30MHz
Carries	7 independent sub-bands,128 carries in a sub-bands, total 896 Sub-carriers
Modulation Technology	OFDM
Multiplex Technology	TDMA+CSMA/CA
RF Output Power	118dBuV
IP Throughput (Max)	100Mbps
Link Attenuation	<70dB (50Mbps@0-60dB, 30Mbps @70dB)
Media and impedance	Coaxial TV Cable 75Ω
Modulation Mode	None,BPSK,QPSK,16QAM,64QAM,256QAM,1024QAM
Management	Telnet, Web, SNMP
User Interface	RF Input Port: F-Type
	Data Port: RJ45
	RF and Data Mix Output : F-Type
Security	Slave authentication, User MAC Amount limitation, Slave Isolation
QoS	802.1p Priority to provide multimedia applications and bandwidth management
Operating Temperature Range	-30—80
Operating Humidity Range	10%--90% No Condensation
Power Consumption	<6w

XD VISION, s.r.o.
Vyšehradská 8
851 06 Bratislava
www.xdvision.sk

pob. Matúškova 7
026 01 Dolný Kubín
Tel.: +421 43 5111 272,3
Fax: +421 43 5111 274
www.xdvision.sk
satdk@xdvision.sk